

espacenet — Bibliographic data

1/1 ページ

Doc 5

**COMMUNICATION TERMINAL DEVICE, TERMINAL COMMUNICATION METHOD, COMMUNICATION PROGRAM AND RECORDING MEDIUM THEREFOR, AND COMMUNICATION SYSTEM** ✓**Publication number:** JP2002185575 (A)**Publication date:** 2002-06-28**Inventor(s):** TODA TOSHIYUKI +**Applicant(s):** MATSUSHITA ELECTRIC IND CO LTD +**Classification:****- international:** H04M1/00; H04M1/725; H04M11/00; H04M1/00; H04M1/72; H04M11/00; (IPC1-7): H04M1/00; H04M1/725; H04M11/00**- European:****Application number:** JP20000375638 20001211**Priority number(s):** JP20000375638 20001211**Abstract of JP 2002185575 (A)**

**PROBLEM TO BE SOLVED:** To provide a communication terminal device, a terminal communication method, a communication program and a recording medium therefor, and a communication system capable of displaying an image desired by a caller to a caller side when an incoming call arrives.

**SOLUTION:** A transmission image coding storing means 6 stores a image code allocated according to an image data selected from an image data storing means 4 storing pairs of an image, and a unique image code allocated to each image data by an image data selecting means 5 for selecting an image data. An image code addition means 7 transmits the image code to an opposite party on a telephone communication. By constructing this way, an image desired by a caller is selected from the range of image data previously stored in common between both caller and called sides on the telephone communication, and is transmitted so that the data quantity transmitted to the opposite party on the telephone communication can be suppressed to be small.

Data supplied from the **espacenet** database — Worldwide